

PRECISION BALANCES (PGW)

- 18 Weighing units (including one custom unit)
- Selectable digital filtering for animal / dynamic weighing
- Adjustable filters
- Simple user-friendly operation
- Full range tare
- Zero Tracking
- Date and time
- Multilingual display
- Large backlit display with dual text prompts
- Capacity tracker
- Large stainless steel pan
- Solid metal housing
- Non-slip adjustable levelling feet
- Lock down mounting slot for Kensington™ type lock
- Colour coded, sealed keypad



Technical Specifications:

Model	PGW 153e	PGW 253e	PGW 453e	PGW 753e	PGW 1502e	PGW 2502e	PGW 3502e	PGW 4502e
Maximum capacity	150g	250g	450g	750g	1500g	2500g	3500g	4500g
Readability	0.001g				0.01g			
Repeatability (S.D.)	0.001g				0.01g			
Linearity (±)	0.002g				0.02g			
Pan size	145x125mm		140x140mm		192x192mm			
Units of measurement	Gram (g), Kilogram (kg), Milligram (mg), Carat (ct), Pound (lb), Ounce (Oz), Dram (d), Grain (GN), Troy Ounce (Ozt), Pennyweight (dWt), Momme (MM), Taels Hk. (TL.H), Taels S. (TL.S), Taels T. (TL.T), Tical (ti), Tola (T), Newton (N), Custom unit							
Typical stabilisation time	2 Sec							
Interface	Bi-directional RS-232 (Standard)							
Calibration	Internal or External, Selectable automatic calibration due to change in time or temperature. "i" models denote internal calibration models.							
Display	Backlit LCD with dual digits (24 mm high) and capacity tracker							
Power supply	15 VDC, 50/60 Hz, 800 mA (Input Voltage 100-240 V, 50/60 Hz)							
Operating temperature	10°C - 40°C							
Housing	Die cast aluminium housing (glass weighing chamber for models with 1mg readability)							
Draught shield	Supplied as standard on models with 1mg readability							
Draught shield dimensions	158x158x80mm							
Overall dimensions (wxdxh)	251x358x104mm							
Net weight	5.5kg							



Standard delivery :

- Main Unit
- Adapter
- Manual