

INTEX Comparator Beam Gauge

Developed to measure both internal and external diameters and lengths, the Intex gauge's aluminium extrusion beam gives it a rigid yet lightweight quality, making it ideal for shop-floor environments. The simple release of a locking thumbscrew enables the gauge's measuring direction to be changed quickly and easily.

 **Bluetooth®**
SMART
Option

WiFi
Option

RS232


Features

- Lightweight and rigid
- Measuring ranges: 200-400mm, 400-600mm, 600-800mm, 800-1000mm
- Sizes over 1000mm available on request
- Internal and external measurement
- 2mm travel on moving contacts
- Adjustable fixed contacts with up to 250mm adjustment range
- Digital or analogue indicator available
- Hardened steel wear pads locate gauge onto component aiding repeatability and prolonging service life
- Setting master required to set the instrument
- Instrument supplied without tooling



INTEXA01

INTEX BEAM GAUGE - WITHOUT INDICATOR

Code No	Range (mm)
INTEX01	200-400
INTEX02	400-600
INTEX03	600-800
INTEX04	800-1000

Code No	Description
INTEXA01	Standard contacts - 10 diameter (pair)

INTEX BEAM GAUGE - With Indicator

Code No	Range (mm)
INTEX01IND	200-400
INTEX02IND	400-600
INTEX03IND	600-800
INTEX04IND	800-1000

INTEX BEAM GAUGE - With Indicator (Bluetooth)

Code No	Range (mm)
INTEX01IND-BT	200-400
INTEX02IND-BT	400-600
INTEX03IND-BT	600-800
INTEX04IND-BT	800-1000

Note: BT denotes Bluetooth